

Heavy Duty Package Dump Body

Warren 451 Series dump bodies are designed for mounting on medium duty single axle truck chassis. They have strong "Stacked Type" understructure for extended life. Engineered for contractors and governmental agencies for hauling sand, gravel, asphalt mix and other materials. Double acting, air operated tailgate with underbody arm or telescopic hoist.



Pictured is a U-10-2430

Features & Benefits of Warren 451 Series Dump Bodies

- •10 Gauge ASTM A1011-45 Sides, Front & Tailgate, 3/16" High Tensile Floor.
- Body, cylinder and NTEA rated hoist manufactured by Warren.
- · Continuous welding throughout body for additional strength.
- Full depth rear corner post with full depth rear crossmember.
- •8" wrap around front corner post



Series 451 Specifications

BODY

Construction: ASTM A1011-45 Hi-tensile steel Understructure: 3"- 4.1#/ft. channel crossmembers

> 5"- 9.0#/ft. channel longitudinals for U10-451 5"- 6.7#/ft. channel longitudinals for F10-451

Floor: 3/16" hi-tensile steel w/2" side to floor radius Sides: 10 ga. steel w/4 x 4 x 1/8" boxed tubing top rail

> 3 per side 6" wide boxed side braces 6" high front & rear gussets w/board pockets 8" full depth rear corner posts & skirt 8" wrap around front corner post, full depth

Dirt shedding rub rails

Tailgate: 10 ga. vertical type—6" higher than sides
Boxed perimeter w/vertical bracing Offset flame

cut steel plate upper hinge Double lower sockets

w/overhooks

Air operated gate latch Double-acting standard 10 ga. steel doghouse

Front Bulkhead: 10 ga. steel doghouse Die-formed horizontal brace

6" higher than sides

Dimensions: Inside -7'3" Width: Outside-8' Length: 10'

Capacity: Struck/sides & ends

U/F451 10' 6/7cu. and 7/8 cu.

HOISTS

U10-451 F10-451 Body Model: Underbody Lift Arm Type: Telescopic Head T10-585 Model: U50-723 1 1/4" dia. 1 1/4" dia. Pivot Pin: 13" 13" Mounting Height: 12" 12" Pivot:

CYLINDER

 Barrel O.D.:
 71¼"
 61½"

 Stage:
 1 stage
 3 stage

 Stroke:
 23"
 85"

ACCESSORIES

LED Lights/Reflectors: Fed Std. 108 - flush mount w/ rubber grommets Hoist mounted

Body Prop: Electric
Back Up Alarm: Cab mounted

Body Up Light

OPTIONAL ATTACHMENTS

Cab Shield - 1/4-19", 3/4-36", half-24", full-43", not installed

Spreader Apron - 8" weld-on, 12" weld-on or 8" Push Apron

Double Acting Hoist - U9- & U10-451

Coal Door - uninstalled



Pictured is a F-10-3238

