



Base model shown with added options

## Dependable Efficiency for the Demanding Workday

Tough and sturdy, the Wabash Cargo XL Body featuring DuraPlate Technology is ideal for effortlessly carrying cargo on shorter, multi-delivery routes. With the ability to turn tight corners, the Cargo XL Body is the solution for quicker delivery to just about anywhere.

### Features

- DuraPlate sidewalls for extreme durability and damage resistance with increased cubes
- One Piece Header System eliminates corner caps, increasing front wall strength
- Flat floor for maximized cargo space
- Step bumper for easy and safe cargo entry
- V-groove threshold protects rear entry and eases cleaning
- Solutions available for traditional, alternative fuel and electrified chassis



## Specifications

WIDTH	LENGTH	HEIGHT		
		79"	85"	91"
<b>86"</b> <small>(Transit only) DRW</small>	12'	•	•	
	14'	•	•	
	15'	•	•	
<b>96"</b> <small>DRW</small>	12'	•	•	
	14'	•	•	
	15'		•	•
	16'		•	•
	17'		•	•

• Available sizes limited by chassis type

FiberPanel® (FRP) not available for 17' lengths



Wind fairing on 85" high model



Translucent roof



Backup camera

<b>Chassis Type</b>	• Cutaway
<b>Truck Body Type</b>	• Dry freight
<b>Sidewalls</b>	• 6mm DuraPlate white panels
<b>Front</b>	<ul style="list-style-type: none"> <li>• FRP Solid bulkhead, setback 4"</li> <li>• FRP white front wall</li> <li>• One-piece aluminum header</li> <li>• Extruded-aluminum radius vertical front corners</li> </ul>
<b>Rear Frame</b>	<ul style="list-style-type: none"> <li>• Painted galvanized steel</li> <li>• 14 ga. header</li> <li>• 12 ga. corner posts</li> <li>• 10 ga. one-piece V-groove threshold</li> <li>• Internal gussets</li> </ul>
<b>Rear Door</b>	<ul style="list-style-type: none"> <li>• Premium roll-up with 6" header</li> <li>• Maximum Security (MS) lock</li> </ul>
<b>Floor</b>	• 18mm hardwood plywood flat floor
<b>Subframe</b>	<ul style="list-style-type: none"> <li>• 3" formed "C"-channel cross members on 16" C/L</li> <li>• High strength 2" channel longills</li> <li>• High strength puck mounted bracket system</li> <li>• Pre-coated understructure</li> </ul>
<b>Roof</b>	<ul style="list-style-type: none"> <li>• One-piece .032" aluminum skin</li> <li>• Galvanized-steel anti-sag roof bows on 24" C/L</li> </ul>
<b>Interior Lights</b>	• LED dome light with rear switch - hot wired

<b>Exterior Lights</b>	<ul style="list-style-type: none"> <li>• LED clearance lights</li> <li>• LED oval taillights with integrated back-up lights - surface mounted</li> </ul>
<b>Bumper</b>	• Pooched step
<b>Warranty</b>	<ul style="list-style-type: none"> <li>• 1-year white surface and leaks</li> <li>• 3-year/36,000-mile limited bulkhead-to-bumper warranty</li> <li>• 5-year limited structural warranty (roof, wall and floor structure)</li> <li>• See our warranty policy for details</li> </ul>

### Options

<b>Front</b>	<ul style="list-style-type: none"> <li>• Wind fairing</li> <li>• Tall cab access door with roof conversion</li> </ul>
<b>Roof</b>	• Translucent roof
<b>Floor</b>	• 2" x 6" dense pine, 1-1/8" laminated hardwood and inverted T extruded aluminum non-slip floor
<b>Rear Door</b>	• Full opening swing door, 48-1/2" or 60" wide roll-up door
<b>Side Door</b>	<ul style="list-style-type: none"> <li>• 32" swing door with aluminum step well</li> <li>• 30" sliding door with aluminum stepwell</li> <li>• 30" or 42" swing side door with stirrup step</li> </ul>
<b>Cargo Control</b>	• Bonded and riveted E-track
<b>Shelving</b>	• Fold-up shelving
<b>Liftgates</b>	• Contact your representative for more information